

## Specifications

| Model          |  | NeoStar B2441S<br>17.9 kW (24 HP Cat.)  | NeoStar B2441S (Narrow)<br>17.9 kW (24 HP Cat.) |
|----------------|--|---|---|
| Engine         | Type                                   | E-TVCS, Liquid Cooled 3-Cylinder Diesel | E-TVCS, Liquid Cooled 3-Cylinder Diesel         |
|                | No. of Cylinders                       | 3                                       | 3   |
|                | Total Displacement                     | 1 123 cc                                | 1 123 cc  |
|                | Maximum Torque                         | 70 Nm                                   | 70 Nm   |
| Transmission   | Clutch                                 | Dry Single Plate                        | Dry Single Plate                                |
|                | Steering                               | Integrated Power Steering               | Integrated Power Steering                       |
|                | Transmission                           | 9F + 3R                                 | 9F + 3R   |
|                | Braking system                         | Wet disk type (OIB)                     | Wet disk type (OIB)                             |
|                | Speed range                            | 2.0 km/h - 19.8 km/h                    | 1.9 km/h - 18.6 km/h                            |
|                | Min. Turning Radius (with brake)       | 2.1 m                                   | 2.1 m   |
| Hydraulic Unit | Hydraulic Control System               | Super Draft & Position Control          | Super Draft & Position Control                  |
|                | Three Point Hitch                      | Category 1, 1N                          | Category 1, 1N                                  |
|                | Max. lift force at lift points         | 750 kg                                  | 750 kg  |
| PTO            | PTO @ Engine Speed                     | 540 @ 2 535 RPM<br>750 @ 2 542 RPM      | 540 @ 2 535 RPM<br>750 @ 2 542 RPM              |
| Capacity       | Fuel Tank                              | 23 l                                    | 23 l  |
| Dimensions     | Overall Length (without 3P)            | 2 407 mm                                | 2 387 mm  |
|                | Overall Width                          | 1 015 mm, 1 105 mm                      | 910 , 1 000 mm                                  |
|                | Overall Height (Top of steering wheel) | 1 280 mm                                | 1 260 mm  |
|                | Wheelbase                              | 1 560 mm                                | 1 560 mm  |
|                | Min. Ground Clearance                  | 325 mm                                  | 300 mm  |
|                | Weight                                 | 655 kg                                  | 625 kg  |
| Tyres          | Front                                  | 17.78 cm x 30.48 cm (7 x 12)            | 12.7 cm x 30.48 cm (5 x 12)                     |
|                | Rear                                   | 21.08 cm x 50.80 cm (8.3 x 20)          | 20.32 cm x 45.72 cm (8 x 18)                    |

### GO SMART IN EVERY NARROW FIELD WITH FARMPower



Italian diaphragm pump & German nozzles

MIST TRAC 600 PLUS

- Delta 75 Udor (Italian) Pump Model
- 20 to 40 Bar Rated Pressure for Spraying, 6 + 6 Nozzle
- 75 LPM Pump Capacity, 600 Lit main tank size

- 2.5 ft - 16 Blades, 3 ft- 20 Blades, J pocket -Japanese make
- 2 & 3 point linkage option, single speed gearbox, chain drive
- 594 mm & 810 mm cutting width, 812 mm & 1 041 mm overall width



Heavy duty gearbox chain

REVERSE-FORWARD ROTAVATOR

Calculated according to our criteria. The actual capacity you achieve may be different. The specifications, information, and appearance of the machines herein are subject to change without notice.



Escorts Kubota Limited, 15/5 Faridabad-121003  
Toll Free No.: 1800 309 1694

Dealer Stamp

SCAN TO KNOW MORE



# NeoStar - B2441S

PERFORMANCE | COMFORT | RELIABILITY



Integrated Power Steering



Unmatched Width 2.98 Ft.



Suspension Seat



ECO - PTO

# EXPERT IN SUGARCANE AND ORCHARD FARMING




**NeoStar** 24 HP Cat.

**B2441S**

**SUSPENSION SEAT**

**SUPER DRAFT CONTROL**

**ECO-PTO**



### E-TVCS ENGINE

24 HP category B2441S with liquid-cooled diesel engine and E-TVCS technology delivers excellent power, high torque, cleaner emissions, low noise and vibration.



### SUSPENSION SEAT

A suspension seat absorbs shocks for a smoother ride. It reduces operator fatigue and improves comfort during long working hours.



### ECO-PTO

ECO-PTO optimizes engine speed for PTO operations-delivering efficient performance with lower fuel consumption.




### SDC

Super Draft Control automatically senses soil resistance and adjusts implement depth-ensuring uniform ploughing and higher efficiency in dry fields.



### 325 MM GROUND CLEARANCE

325 mm ground clearance ensures smooth movement across the fields by protecting the tractor's underbody on uneven terrain.



### MINIMUM TURNING RADIUS

2.1 m turning radius ensures effortless maneuvering in tight rows-perfect for orchard and narrow-row interculture operations.

### COMFORT THAT TRULY SETS NEOSTAR APART



- Best in class 425 mm space
- More leg space
- Comfortable long working hours
- Wider & Flat Platform