

## Specifications

Model		NeoStar B2741S (Narrow) 18.5 kW (27 HP Cat.)
Engine	Type	E-TVCS, Liquid Cooled 3-Cylinder Diesel
	No. of Cylinders	3
	Total Displacement	1 261 cc
	Maximum Torque	81.2 Nm
Transmission	Clutch	Dry Single Plate
	Steering	Integrated Power Steering
	Transmission	9F + 3R
	Braking system	Wet disk type (OIB)
	Speed range	1.9 km/h - 18.6 km/h
	Min. Turning Radius (with brake)	2.1 m
Hydraulic Unit	Hydraulic Control System	Super Draft & Position control
	Three Point Hitch	Category 1, 1N
	Max. lift force at lift points	750 kg
PTO	PTO @ Engine Speed	540 @ 2 535 RPM 750 @ 2 542 RPM
Capacity	Fuel Tank	23 l
Dimensions	Overall Length (without 3P)	2 387 mm
	Overall Width	910 , 1 000 mm
	Overall Height (Top of steering wheel)	1 260 mm
	Wheelbase	1 560 mm
	Min. Ground Clearance	300 mm
	Weight	625 kg
Tyres	Front	12.7 cm x 30.48 cm (5 x 12)
	Rear	20.32 cm x 45.72 cm (8 x 18)

### GO SMART IN EVERY NARROW FIELD WITH FARMPower



Strong  
& Sturdy Design

COMPACT  
ROTAVATOR

- 3.5 ft, 20 & 30 Blades, LC type – Japanese technology
- 970 mm cutting width, 1 220 overall width

- 2.5 ft - 16 Blades, 3 ft- 20 Blades, J pocket -Japanese make
- 2 & 3 point linkage option, single speed gearbox, chain drive
- 594 mm & 810 mm cutting width, 812 mm & 1 041 mm overall width



Heavy duty  
gearbox chain

REVERSE-FORWARD  
ROTAVATOR

Calculated according to our criteria. The actual capacity you achieve may be different. The specifications, information, and appearance of the machines herein are subject to change without notice.



Dealer Stamp

SCAN TO  
KNOW MORE



Escorts Kubota Limited, 15/5 Faridabad-121003  
Toll Free No.: 1800 309 1694



# B

## NeoStar - B2741S - Narrow

PERFORMANCE | COMFORT | RELIABILITY



Integrated  
Power Steering



Unmatched  
Width 2.98 Ft.



2.1 m Turning  
Radius



Powerful  
E-TVCS Engine

\*Terms and conditions apply



# POWERFUL NARROW SPECIALIST


**NeoStar** 27 HP Cat.

**B2741S  
NARROW**

**SUSPENSION SEAT**

**SUPER DRAFT CONTROL**

**ECO-PTO**



### E-TVCS ENGINE

27 HP category B2741S with liquid-cooled diesel engine and E-TVCS technology delivers excellent power, high torque, cleaner emissions, low noise and vibration.



### SUSPENSION SEAT

A suspension seat absorbs shocks for a smoother ride. It reduces operator fatigue and improves comfort during long working hours.



### ECO-PTO

ECO-PTO optimizes engine speed for PTO operations - delivering efficient performance with lower fuel consumption.




### SDC

Super Draft Control automatically senses soil resistance and adjusts implement depth - ensuring uniform ploughing and higher efficiency in dry fields.



### 325 MM GROUND CLEARANCE

325 mm ground clearance ensures smooth movement across the fields by protecting the tractor's underbody on uneven terrain.



### MINIMUM TURNING RADIUS

2.1 m turning radius ensures effortless maneuvering in tight rows - perfect for orchard and narrow-row interculture operations.

### COMFORT THAT TRULY SETS NEOSTAR APART



- Best in class 425 mm space
- More leg space
- Comfortable long working hours
- Wider & Flat Platform