

Specifications

Model		NeoStar B2741S 18.5 kW (27 HP Cat.)
Engine	Type	E-TVCS, Liquid Cooled 3-Cylinder Diesel
	No. of Cylinders	3
	Total Displacement	1 261 cc
	Maximum Torque	81.2 Nm
Transmission	Clutch	Dry Single Plate
	Steering	Integrated Power Steering
	Transmission	9F + 3R
	Braking system	Wet disk type (OIB)
	Speed range	2.0 km/h - 19.8 km/h
	Min. Turning Radius (with brake)	2.1 m
Hydraulic Unit	Hydraulic Control System	Super Draft & Position Control
	Three Point Hitch	Category 1, 1N
	Max. lift force at lift points	750 kg
PTO	PTO @ Engine Speed	540 @ 2 535 RPM 750 @ 2 542 RPM
Capacity	Fuel Tank	23 l
Dimensions	Overall Length (without 3P)	2 407 mm
	Overall Width	1 015 mm, 1 105 mm
	Overall Height (Top of steering wheel)	1 280 mm
	Wheelbase	1 560 mm
	Min. Ground Clearance	325 mm
	Weight	655 kg
Tyres	Front	17.78 cm x 30.48 cm (7 x 12)
	Rear	21.08 cm x 50.80 cm (8.3 x 20) 24.13 cm x 45.72 cm (9.5 x18) optional



Italian diaphragm pump
& German nozzles

**MIST TRAC
600 PLUS**

GO SMART IN EVERY NARROW FIELD WITH FARMPower

- Delta 75 Udor (Italian) Pump Model
- 20 to 40 Bar Rated Pressure for Spraying, 6 + 6 Nozzle
- 75 LPM Pump Capacity, 600 Lit main tank size
- 3.5 ft, 20 & 30 Blades, LCtype – Japanese technology
- 970 mm cutting width, 1 220 overall width



Strong
& Sturdy Design

**COMPACT
ROTAVATOR**

Calculated according to our criteria. The actual capacity you achieve may be different.
The specifications, information, and appearance of the machines herein are subject to change without notice.



Escorts Kubota Limited, 15/5 Faridabad-121003
Toll Free No.: 1800 309 1694

Dealer Stamp

SCAN TO
KNOW MORE



NeoStar - B2741S

PERFORMANCE | COMFORT | RELIABILITY



Integrated
Power Steering



Powerful
E-TVCS Engine



ECO - PTO



Super Draft
Control

*Terms and conditions apply


POWER MEETS VERSATILITY

NeoStar

B2741S

27 HP Cat.

SUSPENSION SEAT | SUPER DRAFT CONTROL | ECO-PTO



E-TVCS ENGINE

27 HP category B2741S with liquid-cooled diesel engine and E-TVCS technology delivers excellent power, high torque, cleaner emissions, low noise and vibration.



SUSPENSION SEAT

A suspension seat absorbs shocks for a smoother ride. It reduces operator fatigue and improves comfort during long working hours.



ECO-PTO

ECO-PTO optimizes engine speed for PTO operations-delivering efficient performance with lower fuel consumption.




SDC

Super Draft Control automatically senses soil resistance and adjusts implement depth-ensuring uniform ploughing and higher efficiency in dry fields.



325 MM GROUND CLEARANCE

325 mm ground clearance ensures smooth movement across the fields by protecting the tractor's underbody on uneven terrain.



MINIMUM TURNING RADIUS

2.1 m turning radius ensures effortless maneuvering in tight rows-perfect for orchard and narrow-row interculture operations.

ENGINEERED FOR EVERY TASK



600L SPRAYER



2B MB PLOUGH



CULTIVATOR 5 TYNE



ROTAVATOR 3.5 FT

COMFORT
THAT TRULY
SETS NEOSTAR
APART



- Best in class 425 mm space
- More leg space
- Comfortable long working Hours
- Wider & Flat Platform