

SPECIFICATIONS

MODEL	SPECIFICATION	MU4502 - 33.1 kW (45 HP Cat.)	
Drive Type		2WD/4WD	
Engine	Engine model name	V2403-M-DI-INT02	
	Rated RPM	2 500	
	Type	Four Stroke Liquid Cooled Diesel Engine	
	Number of Cylinders	4	
	Fuel Tank Volume	60 l	
	Air Cleaner Type	Dry Type, Dual Element	
	Clutch	Dual	
Dimension	Wheelbase	2 000 mm (2WD) 1 990 mm (4WD)	
	Overall length (without 3P)	3 620 mm (2WD) 3 640 mm (4WD)	
	Overall width	1 865 mm (2WD) 1 870 mm (4WD)	
Transmission	Type of Main Shift	Synchromesh	
	Number of Travelling Speed	12F + 4R	
	Travelling Speed @ rated RPM	Forward : 2.1 km/h - 33.3 km/h	
PTO	Type	Independent PTO	
	No. of PTO speed	STD : 540 RPM & 750 RPM OPT : 540 RPM & Rev. PTO	
Hydraulic	Type	Pompa Lift	
	3P Pump Flow Rate	33.2 l/minute	
	Lifting Capacity @ hitch point	1 640 kg	
Steering	Type	Power Steering	
Tyres		2WD	4WD
	Front Tyre Size	15.24 cm x 40.64 cm (6 x 16) 19.05 cm x 40.64 cm (7.5 x 16)	20.32 cm x 45.72 cm (8 x 18) 21.08 cm x 50.80 cm (8.3 x 20)
	Rear Tyre Size	34.54 cm x 71.12 cm (13.6 x 28) 37.84 cm x 71.12 cm (14.9 x 28)	34.54 cm x 71.12 cm (13.6 x 28) High Lug & Low Lug 37.84 cm x 71.12 cm (14.9 x 28) High Lug & Low Lug

Calculated according to our criteria. The actual capacity you achieve may be different.
The specifications, information, and appearance of the machines herein are subject to change without notice.



Disc Harrow



Rotavator Puddling



MB Plough



Trolley



Escorts Kubota Limited, 15/5 Faridabad-121003
Toll Free No.: 1800 309 1694

Dealer Stamp

SCAN TO
KNOW MORE



MU

MU4502

DUM BHI. BHAROSA BHI.



2WD/4WD



*terms & conditions apply

INSPIRED BY KUBOTA GLOBAL DESIGN PHILOSOPHY

MU4502

STYLE & LOOKS



Global Bull
Design

Full LED
Light

Robust Design
& Finish

PRODUCTIVITY



4WD Bevel Gear
Technology

Standard Dual
Clutch

Dual/Reverse
PTO

SMART FEATURES



Pompa Lift

Bonnet Lock

Smart Power
Steering

COMFORT



Flat Deck
Platform

Deluxe Seat

Suspended
Pedals

