

SPECIFICATIONS

MODEL	SPECIFICATION	MU5002 - 36 kW (50 HP Cat.)	
Drive Type		2WD/4WD	
Engine	Engine model name	V2403-M-DI-INT01	
	Rated RPM	2 600	
	Type	Four Stroke Liquid Cooled Diesel Engine	
	Number of Cylinders	4	
	Fuel Tank Volume	60 l	
	Air Cleaner Type	Dry Type, Dual Element	
	Clutch	Dual	
Dimension	Wheelbase	2 005 mm (2WD) 2 000 mm (4WD)	
	Overall length (without 3P)	3 630 mm (2WD) 3 625 mm (4WD)	
	Overall width	1 850 mm (2WD) 1 870 mm (4WD)	
Transmission	Type of Main Shift	Synchromesh	
	Number of Travelling Speed	12F + 4R	
	Travelling Speed @ rated RPM	Forward : 2.1 km/h - 34.5 km/h	
PTO	Type	Independent PTO	
	No. of PTO speed	STD : 540 RPM & 750 RPM OPT : 540 RPM & Rev. PTO	
Hydraulic	Type	Pompa Lift	
	3P Pump Flow Rate	34.5 l/minute	
	Lifting Capacity @ hitch point	1 640 kg	
Steering	Type	Power Steering	
Tyres		2WD	4WD
	Front Tyre Size	15.24 cm x 40.64 cm (6 x 16) 19.05 cm x 40.64 cm (7.5 x 16)	21.08 cm x 50.80 cm (8.3 x 20)
	Rear Tyre Size	37.84 cm x 71.12 (14.9x28)	37.84 cm x 71.12 cm (14.9 x28) High Lung & Low Lug


Calculated according to our criteria. The actual capacity you achieve may be different.
The specifications, information, and appearance of the machines herein are subject to change without notice.



Rotavator



Duckfoot Cultivator



Disc Harrow



MB Plough



Escorts Kubota Limited, 15/5 Faridabad-121003
Toll Free No.: 1800 309 1694

Dealer Stamp

SCAN TO
KNOW MORE



MU

MU5002
DUM BHI. BHAROSA BHI



2WD/4WD



*terms & conditions apply

INSPIRED BY KUBOTA GLOBAL DESIGN PHILOSOPHY

MU5002



STYLE & LOOKS



Global Bull
Design



Full Led
Light



Robust Design
& Finish



PRODUCTIVITY



4WD Bevel Gear
Technology



Standard Dual
Clutch



Dual/Reverse
PTO



SMART FEATURES



Pompa Lift



Bonnet Lock



Smart Power
Steering



COMFORT



Flat Deck
Platform



Deluxe Seat



Suspended
Pedals